



 PRODUCT-DETAILS

M465LR-G2240

35KV ELBOW DB IEC-IEEE NO-SEALING



General Information

Extended Product Type	M465LR-G2240
Product ID	7TAA122220R0039
Catalog Description	35KV ELBOW DB IEC-IEEE NO-SEALING
Long Description	35kV, 630 Amp, Deadbreak Elbow, No Test Point, IEC-IEEE, No Sealing Kit. Cable Insulation Diameter 0.760 to 0.95 inch, Copper Lug, Wire Range 1/0 Stranded/Compressed or 2/0 Solid Compact. 10.36 inch (264.1mm) x 13 inch (330.2mm) from Bottom to Center of Bushing. Includes Elbow Connector Housing, Compression Lug, Stud, Insulated Plug with Cap, Lubricant, Cable Adapter, Installation Instructions and Crimp Chart.

Ordering

UPC	75114392051
Country of Origin	United States (US)
Selling Unit of Measure	each

Container Information

Package Level 1 Units	1 EA
Package Level 1 Width	266.7 mm 10.5 in
Package Level 1 Height	111.252 mm 4.38 in
Package Level 1 Depth / Length	336.55 mm 13.25 in

Additional Information

Application	35kV, 630 Amp Connections
Brand / Label	Elastimold
Color	Black
Connection Type	Compression
Current Rating	630 A
Effective Date	20190108
Enclosure Type	Black
Includes	Elbow Connector Housing, Compression Lug, Stud, Insulated Plug with Cap, Lubricant, Cable Adapter, Installation Instructions and Crimp Chart.
Insulation Material	Yes EPDM Rubber
Material	Housing - EPDM Rubber
Product Name	Terminals, electrical splices and electrical couplings
Product Type	Deadbreak Elbow without Test Point
Size	10.36 inch (264.1mm) x 13 inch (330.2mm) from Bottom to Center of Bushing.
Special Functions	IEC
Standards	ANSI/IEEE Standard 386. IEC Standard
Temperature Range	-40 to +65 °C
Voltage Rating	35 kV

Certificates and Declarations

Data Sheet, Technical Information	M465LR-G2240
-----------------------------------	--------------

Classifications

UNSPSC	39121421
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	4586 >> Electrical connector assembly

Categories

Low Voltage Products and Systems → Installation Products → Cable Accessories and Apparatus → Cable Accessories

