



PRODUCT-DETAILS

K675L2-N2410-S**15-25KV 900A DB SPLICE KIT**Product image
not available**General Information**

Extended Product Type	K675L2-N2410-S
Product ID	7TAA122270R0035
Catalog Description	15-25KV 900A DB SPLICE KIT
Long Description	15/25kv, 900 Amp, Two Way L Kit, Splice, Copper Compression Lug. Cable Insulation Diameter 1.550 inch to 1.780 inch. Conductor Size Compressed Stranded 1000 kcmil. With Sealing Kit - Cold Shrinkable Jacket Seal.

Ordering

UPC	75114244060
Country of Origin	United States (US)
Selling Unit of Measure	each

Container Information

Package Level 1 Units	1 EA
Package Level 1 Width	25.4 mm 1 in

Package Level 1 Height	25.4 mm 1 in
Package Level 1 Depth / Length	25.4 mm 1 in

Additional Information

Application	Used to connect two cable ends and using the two insulating plugs as test points allows for capacitive voltage testing.
Brand / Label	Elastimold
Color	Black
Connection Type	Compression
Current Rating	900 A
Effective Date	20150527
Environmental Conditions	Fully Submersible
Insulation Material	Yes, EPDM Rubber
Material	Housing - EPDM Rubber
Product Name	Terminals, electrical splices and electrical couplings
Product Type	Deadbreak 2-Way L Kit
Size	10.87 inch from Bottom of T to Center of Plug
Special Functions	Cold-Shrinkable Jacket Seal
Standards	ANSI/IEEE Standard 386
Temperature Range	-40 to +65 °C
Voltage Rating	15 to 25 kV

Certificates and Declarations

Data Sheet, Technical Information	K675L2-N2410-S
-----------------------------------	----------------

Classifications

UNSPSC	39121421
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	4586 >> Electrical connector assembly

Categories

Low Voltage Products and Systems → Installation Products → Cable Accessories and Apparatus → Cable Accessories



Product image
not available