



 PRODUCT-DETAILS

656CETP-M0380

COMBO T 600 A CONNECTOR



General Information

Extended Product Type	656CETP-M0380
Product ID	7TAA122410R0184
EAN	5415022187670
Catalog Description	COMBO T 600 A CONNECTOR
Long Description	15kV, 600 Amp Combo T, carries current. Combo Elbow with bus, stud and cable adapter, lug and insulated cap kit. Cable Insulation Diameter 1.370 inch to 1.630 inch. Aluminum Compression Lug. Conductor Size AWG or kcmil, Compressed Stranded 700/750 /Compacted Solid 900.

Ordering

EAN	5415022187670
UPC	75114125253
Country of Origin	United States (US)
Selling Unit of Measure	each

Container Information

Package Level 1 Units	1 EA
Package Level 1 Width	25.4 mm 1 in
Package Level 1 Height	25.4 mm 1 in
Package Level 1 Depth / Length	25.4 mm 1 in

Additional Information

Application	600 Amps, 15kV Connector
Brand / Label	Elastimold
Color	Black
Current Rating	600 A
Effective Date	20130905
Environmental Conditions	All Weatheronditions °C
Includes	Includes Elbow Connector Housing, Stud, Lug, Tube of Lubricant, Cable Adapter, Crimp Chart and Installation Instructions.
Insulation Material	Yes, EPDM Rubber
Material	Housing - EPDM Rubber
Product Name	Terminals, electrical splices and electrcal couplings
Product Type	ComboT Elbow
Size	13.31 inches width, 10.88 inch bottom edge to center of bushing.
Special Functions	Reducing Tap Plug with Stud, Cable Adapter, and Lug. Test Point
Standards	ANSI/IEEE Standard 386
Temperature Range	-40 to +65 °C
Voltage Rating	15 kV

Certificates and Declarations

Data Sheet, Technical Information	656CETP-M0380
-----------------------------------	---------------

Classifications

UNSPSC	39121421
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	4586 >> Electrical connector assembly

Categories

Low Voltage Products and Systems → Installation Products → Cable Accessories and Apparatus → Cable Accessories

