



 PRODUCT-DETAILS

656ETP-G0240-DRG-S

15KV WINDOW OP KIT W-SEALING KIT



General Information

Extended Product Type	656ETP-G0240-DRG-S
Product ID	7TAA122410R0186
EAN	5415022222821
Catalog Description	15KV WINDOW OP KIT W-SEALING KIT
Long Description	600 Series Elbows with IEEE 386 Capacitive Test Points, 600 Amp, 15kV, Test and Ground Connector Kit, Insulated Cap. Cable Insulation Diameter 0.760 inch to 0.950 inch. Aluminum Compression Lug. Conductor Size AWG or kcmil, Compressed Stranded 1/0 /Compacted Solid 2/0. 200ECS Cold-Shrinkable Jacket Seal Included.

Ordering

EAN	5415022222821
UPC	75114155939
Country of Origin	United States (US)
Selling Unit of Measure	each

Container Information

Package Level 1 Units	1 EA
Package Level 1 Width	336.55 mm 13.25 in
Package Level 1 Height	266.7 mm 10.5 in
Package Level 1 Depth / Length	110.998 mm 4.37 in

Additional Information

Application	600 Amps, 15kV
Brand / Label	Elastimold
Color	Black
Connection Type	Compression
Current Rating	600 A
Effective Date	20140116
Insulation Material	Yes, EPDM Rubber
Material	Housing - EPDM Rubber
Product Name	Terminals, electrical splices and electrical couplings
Product Type	Window-Op Connector
Size	Cable Insulation Diameter 0.760 inch to 0.950 inch.
Special Functions	Capacitive Test Point, Insulated Cap and Sealing Kit
Standards	ANSI/IEEE Standard 386
Temperature Range	-40 to +65 °C
Voltage Rating	15 kV

Certificates and Declarations

Data Sheet, Technical Information	656ETP-G0240-DRG-S
-----------------------------------	--------------------

Classifications

UNSPSC	39121421
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	4586 >> Electrical connector assembly

Categories

Low Voltage Products and Systems → Installation Products → Cable Accessories and Apparatus → Cable Accessories

