



 PRODUCT-DETAILS

655CETP-L0360-DRG

15KV 600A DB COMBO-T L0360-DRG



General Information

Extended Product Type	655CETP-L0360-DRG
Product ID	7TAA122430R0081
Catalog Description	15KV 600A DB COMBO-T L0360-DRG
Long Description	600 Amp, 15kV, Combo T Elbow Reducing Tap Plug with Stud, Cable Adapter, Lug and Insulated Cap Kit, No Test Point, Aluminum, Cable Insulation Diameter 1.180 inch to 1.465 inch. Conductor Size AWG or kcmil, Compressed Stranded 650 /Compacted Solid 750 /mmSquared Compact 400.

Ordering

UPC	75114373524
Country of Origin	United States (US)
Selling Unit of Measure	each

Container Information

Package Level 1 Units	1 EA
Package Level 1 Width	25.4 mm

	1 in
Package Level 1 Height	25.4 mm
	1 in
Package Level 1 Depth / Length	25.4 mm
	1 in

Additional Information

Application	600 Amps, 15kV Connector
Brand / Label	Elastimold
Color	Black
Current Rating	600 A
Effective Date	20180531
Environmental Conditions	All Weatheronditions °C
Includes	Includes Elbow Connector Housing, Stud, Lug, Tube of Lubricant, Cable Adapter, Insulated Cap, Crimp Chart and Installation Instructions.
Insulation Material	Yes, EPDM Rubber
Material	Housing - EPDM Rubber
Product Name	Terminals, electrical splices and electrcal couplings
Product Type	ComboT Elbow
Size	13.31 inches width, 10.88 inch bottom edge to center of bushing.
Special Functions	Reducing Tap Plug with Stud, Cable Adapter, Lug and Insulated Cap
Standards	ANSI/IEEE Standard 386
Temperature Range	-40 to +65 °C
Voltage Rating	15 kV

Certificates and Declarations

Data Sheet, Technical Information	655CETP-L0360-DRG
-----------------------------------	-------------------

Classifications

UNSPSC	39121421
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	4586 >> Electrical connector assembly

Categories

Low Voltage Products and Systems → Installation Products → Cable Accessories and Apparatus → Cable Accessories

