K650S-J0330-J0330 1/3



PRODUCT-DETAILS

K650S-J0330-J0330PERMANENT IN-LINE SPLICE



General Information	
Extended Product Type	K650S-J0330-J0330
Product ID	7TAA123400R0016
EAN	5414363445272
Catalog Description	PERMANENT IN-LINE SPLICE
Long Description	15/25kV, Aluminum Permanent In-Line/Straight Splice, Cable Insulation Diameter J - 0.980-1.180 inch, Conductor Size 330 is 500kcmil Stranded/Compressed. Includes EPDM Rubber 1-Piece Housing for Splice.

Ordering	
EAN	5414363445272
UPC	783786625185
Country of Origin	United States (US)
Selling Unit of Measure	each

Container Information	
Package Level 1 Units	1 EA

K650S-J0330-J0330 2/3

Package Level 1 Width	336.55 mm 13.25 in
Package Level 1 Height	266.7 mm
	10.5 in
Package Level 1 Depth /	110.998 mm
Length	4.37 in

Additional Information	
Application	15/25 kV
Brand / Label	Elastimold
Connection Type	Compression
Effective Date	20080508
Insulation Material	EPDM Rubber Housing
Material	Aluminum
Product Name	Terminals, electrical splices and electrical couplings
Product Type	Compression Splice

Certificates and Declarations	
Data Sheet, Technical	K650S-J0330-J0330
Information	

Classifications	
ETIM 6	EC001060 - Crimp splices for aluminium conductor
ETIM 7	EC001060 - Crimp splices for aluminium conductor
ETIM 8	EC001060 - Crimp splices for aluminium conductor
UNSPSC	39121449
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	4669 >> Wire or cable compression splice

Categories

 $Low\ Voltage\ Products\ and\ Systems \rightarrow Installation\ Products \rightarrow Cable\ Accessories\ and\ Apparatus \rightarrow Cable\ Accessories$

K650S-J0330-J0330 3/3

