XPMMS15 1/3



PRODUCT-DETAILS

### XPMMS15

## XPRF MAN MTR STR BOX W/ MS132-32.00



General Information	
Extended Product Type	XPMMS15
Product ID	7TAA137120R0028
Catalog Description	XPRF MAN MTR STR BOX W/ MS132-32.00
Long Description	Explosionproof Manual Motor Starter Enclosure with On / Off Handle, with ABB Type MS132-32 Manual Motor Protectors Suitable for Use with Single and Three Phase Motors, Current Rated for 32.0 Amps, Overall Dimensions Inches: Width 5-3/8, Length 7, Depth 5-5/16, Inside Dimensions Inches: Width 4-1/8, Length 5-7/8, Depth 4, UL Approved for Class I, Division 1 and 2, Groups C and D, Class II, Division 1 and 2, Groups E, F, and G, Copper-free Aluminum with Premium, High Strength Steel Bolts, Zincplated and Coated, C-UL-US Classified Enclosure

Additional Information	
Application	Simple, Compact and Economical Alternative to Conventional Magnetic Motor Controllers for Local Control of a Single Motor
Product Type	Explosionproof Manual Motor Starter Junction Box and Enclosure with On/Off Positions

XPMMS15 2/3

Ordering	
UPC	

#### **Dimensions**

 Product Net Weight
 9 lb

 4.082 kg

# Technical Mounting Type 1/4 or 5/16 Inch Mounting Bolts Number of Batteries 0 Current Rating 32 A Size Width 5-3/8 Inches, Length 7 Inches, Depth 5-5/16 Inches

#### **Environmental**

WEEE Category Product Not in WEEE Scope

#### **Container Information**

Package Level 1 Units	1 EA
Package Level 1 Height	165.1 mm
	6.5 in
Package Level 1 Depth /	263.652 mm
Length	10.38 in
Package Level 1 Width	136.652 mm
· ·	5.38 in

#### **Certificates and Declarations**

Data Sheet, Technical Information	TDS000097
Instructions and Manuals	XPMMS15

#### Classifications

ETIM 8	EC001037 - Motor starter/Motor starter combination
UNSPSC	39121521

786210218205

XPMMS15 3/3

#### Categories

 $Low\ Voltage\ Products\ and\ Systems \rightarrow Installation\ Products \rightarrow Cable\ Protection,\ Explosion\ Proof\ and\ Lighting \rightarrow Hazardous\ Lighting\ \&\ Enclosures$ 

