

PRODUCT-DETAILS

## W20-1BFC AL IR SERVENTR WDGE CLMP/SLDR 1/0 F



| General Information   |   |
|-----------------------|---|
| Extended Product Type | W20-1BFC  |
| Product ID            | 7TAA267150R0005   |
| Catalog Description   | AL IR SERVENTR WDGE CLMP/SLDR 1/0 F   |
| Long Description      | Aluminum Iridated Service Entrance Wedge Clamp and Slider for Wire Range: 1/0-4 ASCR,<br>1/0-4 AAAC, 2/0 Str2 Sol. Flexible Bail, Color Code Blue |
|                       |   |
| Ordering              |   |
| UPC                   | 783786332090  |
| Country of Origin     | Mexico (MX)   |

| Container Information  |                     |
|------------------------|---------------------|
| Package Level 1 Units  | 50 EA               |
| Package Level 1 Width  | 226.06 mm<br>8.9 in |
| Package Level 1 Height | 228.6 mm<br>9 in    |

© 2024 ABB. All rights reserved.

Selling Unit of Measure

Subject to change without notice

each

| Package Level 1 Depth /<br>Length | 350.52 mm<br>13.8 in |
|-----------------------------------|----------------------|
| Package Level 2 Units             | 5600 EA              |
| Package Level 2 Width             | 0 mm<br>0 in         |
| Package Level 2 Height            | 0 mm<br>0 in         |
| Package Level 2 Depth /<br>Length | 0 mm<br>0 in         |

| Application                          | Dead-End Self-supporting Drop Wire. For Extremely Corrosive Areas   |
|--------------------------------------|---|
| Brand / Label                        | Blackburr   |
| Connection Type                      | Tensior   |
| Effective Date                       | 19991027  |
| Insulation Material                  | None  |
| Material                             | Iridited Aluminum   |
| Mounting Type                        | Yes   |
| Number of Conductors                 | 1   |
| Product Name                         | HTS expired or not a valid HTS Number for Canada  |
| Product Type                         | Aluminum Service Wedge Clamp  |
| Size                                 | Length 18-1/2 in X Depth Flexible   |
| Special Functions                    | Drop wire may be cut to exact length for adjustments in drop wire sag. Can be<br>attached to bare neutral at any point in the span. Flexible and rigid bails grip<br>ACSR, AAC and AAAC Conductors. |
| Surface Finishing                    | Bare  |
| Voltage Rating                       | 35 kV   |
| Certificates and Declarations        |   |
| Data Sheet, Technical<br>Information | W20-1BFC  |

**Categories** 

IDEA Granular Category Code (IGCC)

 $\label{eq:low-Voltage-Products-solution} \mbox{Low-Voltage-Products-solution} \mbox{ Apparatus-solution} \mbox{ Distribution} \mbox{ Connectors-solution} \mbox{ Cable-Accessories-and-Apparatus-solution} \mbox{ Distribution} \mbox{ Connectors-solution} \mbox{ Apparatus-solution} \mbox{ App$ 

4601 >> Cable gland connector

W20-1BFC

