



 PRODUCT-DETAILS

R2.5-8NDC-DIN

NYLON-INS 1.5-2.5 RING M8 DIN



General Information

Extended Product Type	R2.5-8NDC-DIN
Product ID	7TCA301120R0050
EAN	5415022422757
Catalog Description	NYLON-INS 1.5-2.5 RING M8 DIN
Long Description	Nylon-Insulated Ring Terminal, DIN, Double Crimp, Length 29.7mm, Width 14mm, Diameter 2.3mm, Stud Size 8mm, Wire Range 1.5-2.5mm ² , Copper, Tin Plated, 600V Max, Temperature Rating 105 Degrees Celsius, Color Blue

Ordering

EAN	5415022422757
UPC	786210150048
Country of Origin	China (CN)
Selling Unit of Measure	each

Container Information

Package Level 1 Units	100 piece
-----------------------	-----------

Package Level 1 Width	1 in 25 mm
Package Level 1 Height	4.72 in 120 mm
Package Level 1 Depth / Length	5.9 in 150 mm
Package Level 2 Units	1200 piece
Package Level 2 Width	5.9 in 150 mm
Package Level 2 Height	3.54 in 90 mm
Package Level 2 Depth / Length	7.08 in 180 mm
Package Level 3 Units	12000 piece
Package Level 3 Width	12.6 in 320 mm
Package Level 3 Height	7.87 in 200 mm
Package Level 3 Depth / Length	18.9 in 480 mm

Additional Information

Brand / Label	Spec-Kon
Color	Blue
Effective Date	20170216
Material	Copper
Product Name	OTHER SWITCHES
Product Type	Nylon-Insulated Ring Terminal
Standards	IEC 60352-2
Voltage Rating	600 V
Wire Size	1.5-2.5 mm ²

Certificates and Declarations

Data Sheet, Technical Information	TDS000446
-----------------------------------	-----------

Classifications

ETIM 6	EC001052 - Solderless copper terminals for copper conductors
ETIM 7	EC001052 - Solderless copper terminals for copper conductors
ETIM 8	EC001052 - Solderless copper terminals for copper conductors
ETIM 9	EC001052 - Solderless copper terminals for copper conductors
UNSPSC	39121432
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	4608 >> Solderless copper terminals for copper conductors

Categories

Low Voltage Products and Systems → Installation Products → Wire Management and Connectivity → Compression & Mechanical Connectors

