




---

 PRODUCT-DETAILS

## VBC7-30-01-F-01

### VBC7-30-01-F-01 Mini Reversing Contactor 24 V DC - 3 NO - 0 NC - Flat-Pin Connections




---

#### General Information

|                       |   |
|-----------------------|---|
| Extended Product Type | VBC7-30-01-F-01   |
| Product ID            | GJL1313903R0011   |
| EAN                   | 4013614217197   |
| Catalog Description   | VBC7-30-01-F-01 Mini Reversing Contactor 24 V DC - 3 NO - 0 NC - Flat-Pin Connections   |
| Long Description      | <p>The VBC7-30-01-F mini reversing contactor is a compact 3 pole contactor with 1 auxiliary contact, flat pin connection and normal mechanical interlock. They are ideally suited for applications where reliability is a must and space is at a premium. Mini reversing contactors are used in residential buldings, commercial buildings and industrial applications for the control of three-phase motor loads up to 5.5 kW (AC-3). Further features are the noiseless and hum-free coil, a switch position indication and the integrated possibility for rail or wall mounting.</p> |

---

#### Ordering

|                        |          |
|------------------------|----------|
| Minimum Order Quantity | 1 piece  |
| Customs Tariff Number  | 85365080 |

---

#### Popular Downloads

|                                   |                 |
|-----------------------------------|-----------------|
| Data Sheet, Technical Information | 1SBC100214C0202 |
| Instructions and Manuals          | 2CDC102046M6801 |
| CAD Dimensional Drawing           | 2CDC001079B0201 |
| Dimension Diagram                 | GJL1200448F0001 |

## Dimensions

|                            |          |
|----------------------------|----------|
| Product Net Width          | 96.2 mm  |
| Product Net Height         | 57.5 mm  |
| Product Net Depth / Length | 46.7 mm  |
| Product Net Weight         | 0.345 kg |

## Technical

|   |  |
|---|--|
| Number of Poles   | 3  |
| Rated Operational Voltage                                   | Auxiliary Circuit 690 V AC<br>Auxiliary Circuit 250 V DC<br>Main Circuit 690 V AC<br>Main Circuit 220 V DC   |
| Rated Frequency (f)   | Main Circuit 60 Hz<br>Main Circuit 50 Hz<br>Main Circuit DC  |
| Rated Impulse Withstand Voltage ( $U_{imp}$ )               | Main Circuit 6 kV  |
| Rated Insulation Voltage ( $U_i$ )                          | 690 V<br>acc. to UL/CSA 600 V  |
| Number of Main Contacts NC                                  | 0  |
| Number of Main Contacts NO                                  | 3  |
| Rated Operational Current AC-1 ( $I_e$ )                    | (220 / 240 V) 40 °C 20 A<br>(220 / 240 V) 55 °C 16 A<br>(380 / 440 V) 40 °C 20 A<br>(380 / 440 V) 55 °C 16 A<br>(690 V) 40 °C 6 A<br>(690 V) 55 °C 6 A |
| Rated Operational Power AC-3 ( $P_e$ )                      | (230 V) Three Phase 3 kW<br>(400 V) Three Phase 5.5 kW<br>(500 V) Three Phase 5.5 kW<br>(690 V) Three Phase, NO 3 kW                                   |
| Rated Short-time Withstand Current Low Voltage ( $I_{cw}$ ) | at 40 °C Ambient Temp, in Free Air, from a Cold State 10 s 96 A  |
| Number of Auxiliary Contacts NC                             | 1  |
| Number of Auxiliary Contacts NO                             | 0  |
| Conventional Free-air Thermal Current ( $I_{th}$ )          | Main Circuit 20 A  |
| Rated Control Circuit Voltage ( $U_c$ )                     | 24 V DC  |
| Coil Operating Limits                                       | (acc. to IEC 60947-4-1) for DC supply 0.85 ... 1.1 x $U_c$ (at $\theta \leq 55$ °C)  |
| Degree of Protection  | Main Circuit Terminals IP20  |
| Pollution Degree  | 3  |
| Mechanical Durability                                       | 10000000 cycle   |

|  |  |
|--|--|
| Minimum Switching Capacity             | Auxiliary Circuit 17 V<br>Auxiliary Circuit 5 mA   |
| Maximum Electrical Switching Frequency | (AC-1) 300 cycles per hour<br>(AC-15) 600 cycles per hour<br>(AC-3) 600 cycles per hour<br>(DC-1) 600 cycles per hour<br>(DC-13) 600 cycles per hour<br>(DC-3) 600 cycles per hour |
| Mounting on DIN Rail                   | TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715<br>TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715   |
| Power Loss                             | at Rated Operating Conditions AC-1 per Pole 1.4 W  |
| Standards                              | IEC/EN 60947-1<br>IEC/EN 60947-4-1<br>IEC/EN 60947-5-1<br>UL 60947-1<br>UL 60947-4-1<br>IEC 60335-2-40 A2L   |

## Technical UL/CSA

|                                  |  |
|----------------------------------|--|
| Maximum Operating Voltage UL/CSA | Main Circuit 600 V AC  |
| Full Load Amps Motor Use         | (115 V AC) Single Phase 13.8 A<br>(200 V AC) Three Phase 7.8 A<br>(220 ... 240 V AC) Three Phase 9.6 A<br>(230 V AC) Single Phase 10 A<br>(440 ... 480 V AC) Three Phase 7.6 A<br>(550 ... 600 V AC) Three Phase 6.1 A |
| Horsepower Rating UL/CSA         | (115 V AC) Single Phase 0.75 Hp<br>(200 V AC) Three Phase 2 Hp<br>(220 ... 240 V AC) Three Phase 3 Hp<br>(230 V AC) Single Phase 1.5 Hp<br>(440 ... 480 V AC) Three Phase 5 Hp<br>(550 ... 600 V AC) Three Phase 5 Hp  |
| General Use Rating UL/CSA        | (600 V AC) 16 A  |
| Contact Rating UL/CSA            | A600   |

## Environmental

|  |  |
|--|--|
| Ambient Air Temperature                    | Operation -20 ... +55 °C<br>Storage -40 ... +80 °C |
| Maximum Operating Altitude Permissible     | 2000 m   |
| Resistance to Shock acc. to IEC 60068-2-27 | 11 ms Pulse 15g                                    |
| Resistance to Vibrations                   | 5g 5 ... 150 Hz                                    |

## Material Compliance

|   |  |
|---|--|
| Conflict Minerals Reporting Template (CMRT) | 9AKK108467A5658  |
| REACH Declaration                           | 2CMT2021-006202  |
| RoHS Information                            | 2CMT2021-006277  |
| RoHS Status                                 | Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019 |
| Toxic Substances Control Act - TSCA         | 2CMT2023-006525  |
| WEEE B2C / B2B                              | Business To Business   |
| WEEE Category                               | 5. Small Equipment (No External Dimension More Than 50 cm)             |

## ABB EcoSolutions

|   |                 |
|---|-----------------|
| Environmental Product Declaration - EPD | 1SAC200410H0001 |
| End of Life Instructions                | 1SBC100156C0263 |

## Certificates and Declarations

|                                  |                     |
|----------------------------------|---------------------|
| A2L Certificate – IEC            | 1SAA938000-4601     |
| CB Certificate                   | 1SAA938000-2002     |
| CQC Certificate                  | CQC2003010304064033 |
| cURus Certificate                | cUL_E191658         |
| Declaration of Conformity - CCC  | 2020980304001854    |
| Declaration of Conformity - CE   | 1SAD101100-3101     |
| Declaration of Conformity - UKCA | 1SAD201100-3101     |
| DNV GL Certificate               | 1SAA938000-0306     |
| EAC Certificate                  | 1SAA920000-2702     |
| KC Certificate                   | 1SAA938000-1501     |
| RMRS Certificate                 | 1SAA938000-0704     |
| UL Certificate                   | E191658-19880915    |

## Container Information

|                                |               |
|--------------------------------|---------------|
| Package Level 1 Units          | box 5 piece   |
| Package Level 1 Width          | 115 mm        |
| Package Level 1 Height         | 54 mm         |
| Package Level 1 Depth / Length | 280 mm        |
| Package Level 1 Gross Weight   | 1.795 kg      |
| Package Level 1 EAN            | 4013614419324 |

## Classifications

|                                    |   |
|------------------------------------|---|
| Object Classification Code         | Q   |
| ETIM 4                             | EC000066 - Magnet contactor, AC-switching |
| ETIM 5                             | EC000010 - Starter combination            |
| ETIM 6                             | EC000010 - Combination of contactors      |
| ETIM 7                             | EC000010 - Combination of contactors      |
| ETIM 8                             | EC000010 - Combination of contactors      |
| eClass                             | V11.0 : 27371009                          |
| UNSPSC                             | 39121529                                  |
| IDEA Granular Category Code (IGCC) | 4763 >> Power contactor, DC switching     |

---

## Categories

---

Low Voltage Products and Systems → Control Products → Contactors → Mini Contactors

