

ACVATIX™

Small valves, actuators + accessories

Product range overview



for radiator, floor heating and chilled ceiling applications

Actuators

- RTN..
- SSA..
- ST..40..
- ST..65

Radiator valves

- VDN1.. / VEN1..
- VDN2.. / VEN2.. / VUN2..
- VPD..-135 / VPE..-135 / VPU..-135

Radiator lockshield valves

- ADN.. / AEN..

Compression fittings

- AVN15-15 / AVN15A16

Adapter

- ASA.. / AV..

Cables

- ASY21.. / ASY61.. / ASY62..

Self-contained thermostatic actuators RTN.. without auxiliary power

- CEN-certified and tested to DIN EN 215 part 1
- UKCA Great Britain conformity
- Absolute noiseless actuator technology
- Manual setpoint adjustment, min. and max. limitation

Favorably priced thermal actuators ST..40 and ST..65.., for demanding requirements

- UKCA Great Britain conformity
- Absolute noiseless actuator technology

Electromotoric actuators SSA.. for the most demanding requirements

- Automatic detection of valve stroke
- Low noise
- Pre-cabled

RF-controlled radiator valve actuator

- SSA955 for integration in Synco system
- SSA911.02ZB for integration in SIEMENS Connected Home

Preadjustable radiator valves VDN.., VEN.., VUN..

- CEN-certified and tested to DIN EN215 part 1
- UKCA Great Britain conformity
- Insert can be replaced while plant is under pressure


Pressure compensated radiator valves VPD.., VPE.., VPU.. (PICV) for perfect hydraulic balancing

- Low noise operation
- No additional line balancing required
- Hydraulic balancing is considerable simplified
- Creates comfort and saves energy

Various mounting accessories

- Simple and fast mounting
- High operation safety

Equipment combinations: Thermostatic and electronic actuators, valves and fittings













Thermostatic actuators (without auxiliary power)



RTN51/RTN51G	RTN71	RTN81
		

Electric actuators (with auxiliary power)

SSA118.. / SSA131.. / SSA161.. / SSA331..	ST..40.. / ST..65..	SSA955	SSA911..
			

Radiator valves			
DIN	DIN215	NF	DIN
VDN110 (3/8") VDN115 (1/2") VDN120 (3/4")	VPD110..-135 (3/8") VPD115..-135 (1/2") VPD120..-135 (3/4")	VPD210..-135 (3/8") VPD215..-135 (1/2") VPD220..-135 (3/4")	VDN210 (3/8") VDN215 (1/2") VDN220 (3/4")
			
VEN110 (3/8") VEN115 (1/2") VEN120 (3/4")	VPE110..-135 (3/8") VPE115..-135 (1/2") VPE120..-135 (3/4")	VPE210..-135 (3/8") VPE215..-135 (1/2") VPE220..-135 (3/4")	VEN210 (3/8") VEN215 (1/2") VEN220 (3/4")
			
	VPU110A-135 (3/8") VPU115A-135 (1/2")		VUN210 (3/8") VUN215 (1/2")
			

Radiator lockshield valves	
ADN10 (3/8") ADN15 (1/2") ADN20 (3/4")	AEN10 (3/8") AEN15 (1/2") AEN20 (3/4")
	






Compression fittings	
For copper and soft pipes	For plastic pipes with aluminum foil
AVN15-15	AVN15A16
	

Adapter (AV..)

For mounting

- thermostatic actuators RTN..
- electromotoric actuators SSA..
- RF-controlled actuator SSA955

on radiator valves of other manufacturer according to table:

AV.. adapters for Siemens actuators for TRV valves of other manufacturers	AV52 ¹⁾	AV53	AV54	AV55	AV57	AV58	AV59 ¹⁾	AV60 ¹⁾	AV61
									
	Comap	Danfoss RA-N	Danfoss RAVL	Danfoss RAV	Herz	Oventrop < 2002	Vaillant	TA < 2002	MMA Markaryd
Adapter thread	M28 x 1,5	-	-	-	M28 x 1,5	M30 x 1	-	M28 x 1,5	M28 x 1,5
Stock number	BPZ: AV52	BPZ: AV53	BPZ: AV54	BPZ: AV55	BPZ: AV57	BPZ: AV58	BPZ: AV59	BPZ: AV60	BPZ: AV61

¹⁾ Also compatible with thermal actuators ST..40.. and ST..65.. in combination with ASA80 adapter.

Adapter (ASA..)

For mounting

- thermal actuators St..40.. und ST..65..

on radiator valves of other manufacturer according to table:

ASA..Adapter for Siemens actuators for TRV valves of other manufacturers	ASA04H	ASA10	ASA26	ASA59	ASA72	ASA78	ASA80
							
	Beulco Floorheating	Strawa Floorheating	Giacomini	Danfoss RAV/L	Danfoss RAV	Danfoss RA	M28 x 1,5
Adapter thread	M30 x 1,5	M30 x 1,5	M30 x 1,5	M30 x 1,5	M30 x 1,5	M30 x 1	M30 x 1,5
Stock number	S55845-Z304	S55845-Z305	S55845-Z299	S55845-Z300	S55845-Z301	S55845-Z302	S55845-Z303

Cable

for actuators ST..121.65/00 and ST..321.65/00	ASY21L10	ASY21L20	ASY21L50	ASY21L100	ASY21L10H	ASY21L50H	ASY21L100H
	PVC cable				Halogen free cable		
Cable length	1 m	2 m	5 m	10 m	1 m	5 m	10 m
Stock number	S55845-Z304	S55845-Z305	S55845-Z299	S55845-Z300	S55845-Z301	S55845-Z302	S55845-Z303

For actuators ST..161.65L10 and ST..162.65L10	ASY61L10	ASY61L20	ASY61L50	ASY61L100	ASY61L10H	ASY61L50H	ASY61L100H
	PVC cable no position feedback				Halogen free cable no position feedback		
Cable length	1 m	2 m	5 m	10 m	1 m	5 m	10 m
Stock number	S55845-Z285	S55845-Z286	S55845-Z287	S55845-Z288	S55845-Z289	S55845-Z290	S55845-Z291

For actuators ST..161.65L10 and ST..162.65L10	ASY62L10	ASY62L20	ASY62L50	ASY62L100	ASY62L10H	ASY62L50H	ASY62L100H
	PVC cable position feedback				Halogen free cable position feedback		
Cable length	1 m	2 m	5 m	10 m	1 m	5 m	10 m
Stock number	S55845-Z292	S55845-Z293	S55845-Z294	S55845-Z295	S55845-Z296	S55845-Z297	S55845-Z298

Type reference (alphabetical)

Actuators

Type reference	Stock number	Description	Thread inch ¹	Design	Data sheet	
RTN51..	BPZ:RTN51..	Thermostatic actuator • white (RAL 9016) • glossy or matt appearance	M30x1,5	Self acting	N2111	
RTN71	BPZ:RTN71	Thermostatic actuator		with remote sensor		
RTN81	BPZ:RTN81			with remote adjuster		
SSA118.09HKN	S55180-A111	Electromotive actuator		DC 24 V	A6V11858280	
SSA131.00	S55180-A106			AC 24 V	A6V11858276	
SSA151.05H	S55180-A110			AC / DC 24 V	A6V11858278	
SSA161.05	S55180-A107				A6V11858276	
SSA161.05HF	S55180-A108				A6V11858278	
SSA161E.05HF	S55180-A109			AC 230 V	N4893	
SSA31	BPZ:SSA31				A6V11858276	
SSA331	S55180-A105			AC / DC 24 V	N4893	
SSA61	BPZ:SSA61					
SSA81	BPZ:SSA81			AC 24 V		
SSA911.02ZB	S55181-A105			Wireless radiator valve actuator, works with SIEMENS Connected Home	Battery-powered (1,5 V / AA)	A6V13722083
SSA955	BPZ:SSA955			RF-controlled actuator for radiator valves, Synco 900	Battery-powered (LR6 / AA)	N2700
STA121.40L10	S55174-A219			Thermal actuators	AC/DC 24 V	A6V14028280
STA121.65/00	S55174-A211					
STA121.65H20	S55174-A208					
STA121.65L10	S55174-A201					
STA121.65L20	S55174-A205					
STA126.40L10	S55174-A225					
STA161.40L10	S55174-A222	AC 24 V				
STA161.65L10	S55174-A219	AC/DC 24 V				
STA162.65L10	S55174-A216					
STA321.40L10	S55174-A218	AC 230 V				
STA321.65/00	S55174-A210					
STA321.65H20	S55174-A209					
STA321.65L10	S55174-A200					
STA321.65L20	S55174-A204					
STA326.40L10	S55174-A224					
STP121.40L10	S55174-A221	AC/DC 24 V				
STP121.65/00	S55174-A213					

Type reference	Stock number	Description	Thread inch ¹	Design	Data sheet
STP121.65L10	S55174-A203	Thermal actuators	M30x1,5	AC/DC 24 V	A6V14028280
STP121.65L20	S55174-A207				
STP161.40L10	S55174-A223			AC 24 V	
STP161.65L10	S55174-A215				
STP162.65L10	S55174-A217			AC/DC 24 V	
STP321.40L10	S55174-A220				
STP321.65/00	S55174-A212				
STP321.65L10	S55174-A202			AC 230 V	
STP321.65L20	S55174-A206				

Valves

Type reference	Stock number	Description	Thread inch ¹	Design	Data sheet
VDN110	BPZ:VDN110	Radiator valves	3/8	straight, DIN	N2105
VDN115	BPZ:VDN115		1/2		
VDN120	BPZ:VDN120		3/4		
VDN210	BPZ:VDN210		3/8	straight, NF	N2106
VDN215	BPZ:VDN215		1/2		
VDN220	BPZ:VDN220		3/4		
VEN110	BPZ:VEN110		3/8	angle, DIN	N2105
VEN115	BPZ:VEN115		1/2		
VEN120	BPZ:VEN120		3/4		
VEN210	BPZ:VEN210		3/8	angle, NF	N2106
VEN215	BPZ:VEN215		1/2		
VEN220	BPZ:VEN220		3/4		
VUN210	BPZ:VUN210		3/8	reverse angle, NF	
VUN215	BPZ:VUN215		1/2		
VPD110A-135	S55264-V165		Radiator valves PICV (2-port)	3/8	
VPD115A-135	S55264-V166	1/2			
VPD120A-135	S55264-V167	3/4			
VPD210A-135	S55264-V173	3/8		straight, DIN 215 F	
VPD215A-135	S55264-V174	1/2			
VPD220A-135	S55264-V175	3/4			
VPE110A-135	S55264-V168	Radiator valves PICV (Angle)	3/8	straight, DIN 215 D	
VPE115A-135	S55264-V169		1/2		
VPE120A-135	S55264-V170		3/4		
VPE210A-135	S55264-V176		3/8	straight, DIN 215 F	
VPE215A-135	S55264-V177		1/2		
VPE220A-135	S55264-V178		3/4		
VPU110A-135	S55264-V171	Radiator valves PICV (Axial)	3/8	straight, DIN 215 D	
VPU115A-135	S55264-V172		1/2		

Accessories

Typ reference	Stock number	Description	Thread inch ¹	Design	Data sheet
ADN10	BPZ:ADN10	Radiator lockshield valves	3/8	straight	N2107
ADN15	BPZ:ADN15		1/2		
ADN20	BPZ:ADN20		3/4		
AEN10	BPZ:AEN10		3/8	angle	
AEN15	BPZ:AEN15		1/2		
AEN20	BPZ:AEN20		3/4		
ALE10	BPZ:ALE10	Electronic Δp manometer, 7 bar	M30 × 1,5		A6V13089932
ALE12	S55264-V188	Tool for measuring differential pressure, Adapter with tube			
ASA04H	S55845-Z304	Adapter for radiator valves from other manufacturers			
ASA10	S55845-Z305				
ASA26	S55845-Z299				
ASA59	S55845-Z300				
ASA72	S55845-Z301				
ASA78	S55845-Z302				
ASA80	S55845-Z303				
ATN4	BPZ:ATN4	Manual knob			-
ATN6	S55264-V187		-	-	A6V13089932
AV52	BPZ:AV52	Adapter for radiator valves from other manufacturers	M28 × 1,5		N2100
AV53	PBZ:AV53		-		
AV54	PBZ:AV54		-		
AV55	PBZ:AV55		-		
AV57	PBZ:AV57		M28 × 1,5		
AV58	PBZ:AV58		M30 × 1,5		
AV59	PBZ:AV59		-		
AV60	PBZ:AV60		-		
AV61	PBZ:AV61		M28 × 1,5		
AVN15-15	BPZ:AVN15-15		Compression fittings for copper and soft steel pipes		
AVN15A16	BPZ:AVN15A16	Compression fittings for plastic pipes with aluminum foil	Connection valve side Tube ø 16 × 2 mm		

¹⁾ Connection pipe side

NO, NC valves

NO valves	<ul style="list-style-type: none"> Fully open when de-energized (normally open) Valve stem extended Radiator valves like VDN.., VEN.., VUN.., VPD.., or VPU:: VPE.. are usually NO valves.
NC valves	<ul style="list-style-type: none"> Closed when de-energized (normally closed) Valve stem extended Small valves like V..P47.. are usually NC valves.

Valve and actuator combinations

NO function	<ul style="list-style-type: none"> Actuator stem is retracted when de-energized. Valve is open.
NC function	<ul style="list-style-type: none"> Actuator stem is extended when de-energized. Valve is closed.

RTN..

The thermostatic RTN.. actuators control the heat demand. They control the water flow by opening and closing the radiator valves.

- With increased heat demand the actuator stem retracts and steadily opens the radiator valve.
- With decreasing heat demand the actuator stem extends and steadily closes the radiator valve.

STA..

Radiator valves (NO valves)	STA actuator de-energized
<ul style="list-style-type: none"> VDN.., VEN.., VUN.. VPD.., VPE.. 	closed (NC function)

SSA..

The electromotive actuator is driven by DC 0...10 V (SSA61) positioning signal or by a 3-position signal (SSA31, SSA81). The description of operation in this document applies to the valve versions which are fully open when de-energized (NO).

3-position control signal

- Voltage at Y1: Stem reacts: valve opens
- Voltage at Y2: Stem extends: valve closes
- No voltage at Y1 and Y2: Actuator maintains its current position

DC 0...10 V

- The valve opens / closes in proportion to the control signal at Y.
- At DC 0 V, the valve is fully closed (A □ AB), stem extended
- When power supply is removed, the actuator maintains its current position.

Issued by
Siemens Switzerland Ltd
Smart Infrastructure
Global Headquarters
Theilerstrasse 1a
CH-6300 Zug
+41 58 724 2424
www.siemens.com/buildingtechnologies

© Siemens Switzerland Ltd, 2006
Technical specifications and availability subject to change without notice.

Document ID CE1N2100en
Edition 2023-09-27