



TEL (915) 590-8500  
FAX (915) 590-8510

4.63"

**Cat. No. HHN322N**      **Fusible Heavy Duty Safety Switch**      **Type VB II**  
**60 Amps Maximum**      **240 Volts AC(V~) Maximum**      **250 Volts DC(V-DC) Maximum**  
**Type 1**      **Indoor**      **Suitable for use as Service Equipment**

Horsepower Ratings	240 VAC 1Ø	240 VAC <sup>2</sup> 3Ø	250 VDC
Std. HP (Std. Fuse) <sup>4</sup>	3	7½	10
Max. HP (Time Delay)	10	15	—

Continuous load current not to exceed 80% of the rating of fuses employed in other than motor circuits.

**Fuse and Short Circuit Information**

When used with Class K fuses, Class H fuses or a UL Listed Circuit Breaker rated for 10,000 amperes, RMS symmetrical, 240 volts maximum, this switch is suitable for use on a circuit capable of delivering not more than 10 000 amperes, RMS symmetrical, 240 volts, maximum.

When used with Class R fuses and Class R fuse clip kit **HR612M** properly installed, this switch is suitable for use on a circuit capable of delivering not more than 200,000 amperes, RMS symmetrical, 240 volts maximum.

**Danger** – Unless Class R fuses are used, this switch may present a risk of fire and injury to persons if installed on circuits capable of delivering more than 10,000 amperes, RMS symmetrical.

When used with fuses marked with DC ratings, this switch is suitable for use on a circuit capable of delivering not more than the DC interrupting rating marked on the fuse, at the DC voltage rating marked on the fuse, up to a maximum of 10,000 amperes, 250 volts DC.

**Danger** – Unless fuses marked for an interrupting rating of 10,000 amperes at 250 volts DC are used, this switch may present a risk of fire and injury to persons if installed on circuits capable of delivering more than 10,000 amperes.

**Renewable link fuses are not recommended**

DANGER

**Hazardous voltage.**  
**Will cause death or serious injury.**

- Disconnect and lock out power supplying this switch before working on this switch.
- Turn off switch before removing or installing fuses if so equipped.
- Always use a properly rated voltage sensing device on all fuse clips (Fusible) or all load side terminals (Non-Fusible) to confirm switch is off.
- Close or replace cover before turning power on.

+ - - - **USE 60°C / 75°C COPPER OR ALUMINUM WIRE**

**Terminal & Wire Information**

Description	Wire Range	Wire Tightening Torque <sup>5</sup>	Lug Mounting Torque <sup>5</sup>
<b>Line, Load &amp; Main Neutral</b>	14-2 AWG	35 lb-ins. 14-10 AWG / 40 lb-ins. 8 AWG 45 lb-ins. 6-4 AWG / 50 lb-ins. 3-2 AWG	80 lb-ins.
<b>Service Ground</b>	14-4 AWG	35 lb-ins. 14-10 AWG / 40 lb-ins. 8 AWG 45 lb-ins. 6-4 AWG	24 lb-ins.

Inspection record number:

**Accessories**

Aux. Switch (1NO-1NC)	HA161234M	Neutral	HN623M	Class R Fuse Kit (Rejects Class H & K Fuses)	HR612M
Aux. Switch (2NO-2NC)	HA261234M	Ground Lug Kit (Wire Range 14-4 AWG)	HG61234M	Shield Kit	HSK62SSW

**Replacement Parts**

Line Base	HFB22	Wire Grip Kit (AL)	HL612	Handle / Handle Guard	HH6123
Load Base	HBB22	Mechanism	HM6123	Door	

Protected by one or more of the following US Patents: 6,134,979, 6,356,460, 5,945,650, 5,990,439.

<sup>2</sup> Suitable for 3-Phase, 3-Wire, Grounded B-Phase Systems

<sup>4</sup> The starting current of motors more than the standard horsepower or kilowatt ratings may require the use of fuses with appropriate time delay characteristics.

<sup>5</sup> When tightening or replacing connectors, refer to lug mounting torque in Terminal & Wire Information Table.

For questions on this device please call 1-800-964-4114



**Murray Electrical Products**  
Siemens Industry, Inc.  
Norcross, GA 30092 USA  
<http://www.murrayelectrical.com>  
Assembled in Mexico

Pc. No. 502122A09  
1003



R .125"  
X4

**Due to the variances among computer monitors and printers, the depictions of the colors you see may not be a true representation of the final color job, these colors are only for proofing. If close color matching is a requirement of the job, then you must let us know at the beginning of the job and specify PMS colors or otherwise provide color samples.**

PART NO. **502122A09**  
**A7B91501321680**

COMPANY NAME	MATERIAL	SIZE	JOB WILL NOT BE PRINTED UNLESS APPROVED BY CUSTOMER.	
Siemens Industry, Inc. (MTR)	Synthetic Paper Lamination: <b>INK COLORS</b> Black Red 185	WIDTH 4.63"	<input type="checkbox"/> OK TO PRINT AS IS	<input type="checkbox"/> MAKE CORRECTIONS, RESUBMIT CORRECTED PROOF
		LENGTH 7.44"	<input type="checkbox"/> OK TO PRINT WITH CORRECTIONS AS MARKED	
		OFFSET .125"	<b>AUTHORIZED BY</b>	<b>DATE</b>

DWG NO.	501010xls 41P
DESCRIPTION:	Label
REVISION LEVEL	41P
DESIGNER	Gibran Camacho
CHECKED BY	
DATE	06/29/12

THIS DOCUMENT IS THE PROPERTY OF LABELTECH, INC. IT'S USE IS AUTHORIZED ONLY FOR RESPONDING TO A REQUEST FOR QUOTATION OR FOR THE PERFORMANCE OF WORK REQUESTED FROM LABELTECH, INC. ALL QUESTIONS MUST BE REFERRED TO THE LABELTECH, INC. PRODUCTION DEPARTMENT.