


Connecting cable

NHSB-A1-30-BLG3-LE3-PU8-2XBB

Part number: 1686614

FESTO

Suitable for use with linear actuator DFPI.



Data sheet

| Feature | Value |
|--|--|
| Protective tube length | 30 m |
| Assembly position | Any |
| Outdoor use | C1 - weather protected locations of use |
| Operating voltage range DC | 0 ... 30 V |
| Relative air humidity | 5 - 100 % Condensing |
| Protection class | IP65 IP67 IP68 IP69K NEMA 4 |
| Ambient temperature | -20 ... 60 °C |
| Ambient temperature with flexible cable installation | -5 ... 60 °C |
| Electrical connection 1 | Straight plug, 3-pin |
| Electrical connection 2 | Open end, 3-wire |
| Operating medium | Compressed air in accordance with ISO8573-1:2010 [7:4:4] |
| Note on operating and pilot medium | Lubricated operation possible |
| Pneumatic connection | For tubing outside diameter 8 mm |
| Min. cable bending radius | 100 mm |
| Cable structure | 3 x 0,75 mm ² |
| Product weight | 7,500 g |
| Materials note | Contains PWIS substances Conforms to RoHS |
| Materials information for conduit | PA |
| Information on materials, protective conduit fitting | PA |
| Materials information, cable sheaths | PVC |
| Materials information for seals | TPE |