


Pressure sensor SDE3-D10M-B-WQ4-2P-M12

Part number: 568666

FESTO



Data sheet

| Feature | Value |
|--|---|
| Certification | RCM compliance mark c UL us - Recognized (OL) |
| CE marking (see declaration of conformity) | As per EU EMC directive |
| UKCA marking (see declaration of conformity) | To UK instructions for EMC To UK RoHS instructions |
| Note on materials | RoHS-compliant |
| Measured variable | 1x relative pressure/1x differential pressure |
| Method of measurement | Piezoresistive pressure sensor with display |
| Pressure measuring range initial value | 0 bar |
| Pressure measuring range end value | 10 bar |
| Operating medium | Compressed air as per ISO 8573-1:2010 [7:4:4] |
| Information on operating and pilot media | Operation with oil lubrication possible |
| Temperature of medium | 0 °C...50 °C |
| Ambient temperature | 0 °C...50 °C |
| Accuracy in ± % FS | 2 %FS |
| Switching output | 2xPNP |
| Switching function | Freely programmable |
| Switching element function | Switchable |
| Reproducibility of switching value | 0,3 % |
| Max. output current | 100 mA |
| Short-circuit protection | Pulsed |
| DC operating voltage range | 15 V...30 V |
| Reverse polarity protection | for all electrical connections |
| Electrical connection 1, connection type | Plug |
| Electrical connection 1, connection technology | M12x1 A-coded as per EN 61076-2-101 |
| Electrical connection 1, number of pins/wires | 5 |
| Electrical connection 1, type of mounting | Screw-type lock |
| Type of mounting | With through-hole With H-rail With wall/surface bracket |
| Mounting position | Any |
| Pneumatic connection | QS-4 |

| Feature | Value |
|----------------------------------|-------------------------------|
| Product weight | 37 g |
| Housing material | PA-reinforced PC |
| Display type | Illuminated LCD |
| Switching status indication | LCD yellow |
| Setting options | Teach-in |
| Protection against tampering | PIN code |
| Setting range threshold value | 0 %...100 % |
| Setting range hysteresis | 0 %...90 % |
| Degree of protection | IP65 |
| Corrosion resistance class (CRC) | 2 - Moderate corrosion stress |
| LABS (PWIS) conformity | VDMA24364-B1/B2-L |