



Note:
 - Drawings Not To Scale
 - Drawings Subject to Change Without Notice
 - Dimensions are inches next to [Millimeters]

Part No.:
LR3D3136

Schneider Electric
 Schneider Electric United States
 North American Division
 Boston One Campus
 800 Federal Street
 Andover, MA 01810, USA
 Phone: +1 8773425173
 Email: CCC@us.schneider-electric.com

Technical Information:

Termination Method:	Ring-Tongue
UL File/CCN:	E164353 / NKCR
CSA File:	LR43364 3211 03
Meets Standard:	IEC 60947-1
CE:	Yes
RoHS:	Yes
Weight:	0.84 lb (0.38 kg)
Power Wire Size :	See Chart for Lug
Control Wire Size:	Lug Size 0.32 in (8mm)
Power Terminal Torque:	70 lb-in (8 Nm)
Control Terminal Torque:	15 lb-in (1.7 Nm)
Mtg. Directly to Contactor:	Yes
Mtg. Separate from Contactor:	LA7D3064

Specification:

Description:	TeSys D IEC Overload Relays, Amb. Comp. Bimetallic Class 10 wo Single Phase Sensitivity
Type:	TeSys D IEC Bi-Metallic Overload Relay with Everlink 600V 13A
Ambient Comp. Bimetallic:	Yes
Solid State:	No
Class 10:	Yes
Class 20:	No
Single Phase Sensitivity:	No
For Use with Contactors:	LC1D40A thru LC1D65A
Current Setting Range:	9A to 13A