



Note:

- Drawings Not To Scale
- Drawings Subject to Change Without Notice
- Dimensions are inches next to [Millimeters]

Part No.:

XBTGT5330



Schneider Electric United States
 North American Division
 Boston One Campus
 800 Federal Street
 Andover, MA 01810, USA
 Phone: +1 8773425173
 Email: CCC@us.schneider-electric.com

Technical Information:

North America Certifications: UL 508, UL 1604, CSA C22-2 no. 14
 IEC, CE Certifications: EN 61131-2, IEC 61000-6-2, CE
 FCC & EMC: FCC (Class A), C-Tick
 Applicable Machine Safety Std.: Class 1 Div 2 T4A or T5 (UL and CSA), ATEX Zone 2/22
 Marine Certifications: ABS, BV, DNV, GL, LR, RINA, RMRS, RRR
 Other Certifications: ACA, GOST
 Common Automation Protocols: Modbus, Uni-TE, Modbus TCP/IP, FIPWAY, FIPIO, Modbus Plus
 Other Protocols: PacDrive, Siemens, Omron, Mitsubishi, Rockwell
 Operating Temperature Range: 0c to 50c
 Storage Temperature Range: -20c to +60c
 Relative Humidity: 0 to 90% non condensing

Description:

Screen Type: 65k Color TFT
 Resolution: 640 x 480 pixels (VGA), 311 cd/m2
 Interface Ports: SUB-D9 (RS 232C/RS 422/485 serial link), RJ45 (RS485)
 Ethernet Ports: Ethernet IEEE 802.3 10/100 Base-T (RJ 45)
 USB Ports: Type A (V1.1)
 Operating System: 0 audio out, 1 discrete in, 3 discrete out
 Enclosure Rating: IP65, NEMA 4X indoor
 Processor: 266 Mhz RISC
 SRAM: 512k
 Storage: 32M EPROM
 Supply Voltage: 24 VDC

Specification: