

MTG300 MTY300 Thyristor Modules(Non-isolated Type)


Features:

- n Non-Isolated. Mounting base as common
- n Pressure contact technology with
Increased power cycling capability
- n Low on-state voltage drop

Typical Applications

- n Welding Power Supply
- n Various DC Power supplies
- n DC supply for PWM inverter

$I_{T(AV)}$ **300 A**
 V_{DRM}/V_{RRM} **800~1800 V**
 I_{TSM} **9.6 A × 10³**
 I^2t **470 A² S × 10³**



SYMBOL	CHARACTERISTIC	TEST CONDITIONS	T _j (°C)	VALUE			UNIT
				Min	Type	Max	
I _{T(AV)}	Mean on-state current	180° half sine wave 50Hz Single side cooled, T _c =90°C	125			300	A
I _{T(RMS)}	RMS on-state current		125			471	A
V _{DRM} V _{RRM}	Repetitive peak off-state voltage Repetitive peak reverse voltage	V _{DRM} &V _{RRM} tp=10ms V _{DSM} &V _{RSM} = V _{DRM} &V _{RRM} +200V respectively	125	800		1800	V
I _{DRM} I _{RRM}	Repetitive peak current	at V _{DRM} at V _{RRM}	125			25	mA
I _{TSM}	Surge on-state current	10ms half sine wave	125			9.60	KA
I ² t	I ² T for fusing coordination	V _R =60%V _{RRM}				470	A ² S*10 ³
V _{TO}	Threshold voltage		125			0.80	V
r _T	On-state slop resistance					0.72	mΩ
V _{TM}	Peak on-state voltage	I _{TM} =900A	25			1.58	V
dv/dt	Critical rate of rise of off-state voltage	V _{DM} =67%V _{DRM}	125			800	V/μs
di/dt	Critical rate of rise of on-state current	Gate source 1.5A t _r ≤0.5μs Repetitive	125			100	A/μs
I _{GT}	Gate trigger current	V _A =12V, I _A =1A	25	30		150	mA
V _{GT}	Gate trigger voltage			1.0		2.5	V
I _H	Holding current			20		200	mA
V _{GD}	Non-trigger gate voltage	At 67%V _{DRM}	125	0.2			V
R _{th(j-c)}	Thermal resistance Junction to case	Single side cooled				0.080	°C /W
R _{th(c-h)}	Thermal resistance case to heat sink	Single side cooled				0.04	°C /W
F _m	Thermal connection torque (M8)				12		N·m
	Mounting torque (M6)				6		N·m
T _{stg}	Stored temperature			-40		125	°C
W _t	Weight				680		g
Outline	404F4						




Fig.1




Fig.2




Fig.3




Fig.4




Fig.5




Fig.6




Fig.7




Fig.8




Fig.9




Fig.10

Outline:

